

# Industrial Line

**Rigid scopes**



## Technical data

### Standard

#### Ø 2.7mm

Length	DoV	FoV	Type
175mm	0°	80°	Rigid
175mm	0°	80°	Semi
175mm	30°	80°	Rigid
175mm	30°	80°	Semi
175mm	70°	80°	Rigid

#### Ø 4.0mm

Length	DoV	FoV	Type
175mm	0°	80°	Rigid
175mm	0°	0°	Semi
175mm	30°	80°	Rigid
175mm	30°	80°	Semi
175mm	45°	80°	Rigid
175mm	70°	80°	Rigid
302mm	0°	80°	Rigid
302mm	0°	80°	Semi
302mm	30°	80°	Rigid
302mm	30°	80°	Semi

### With Mirror tube

#### Ø 1.9mm

Length	DoV	FoV	Mirror tube
bis zu			
240mm	0°	45°	90°/2.7mm
Ø 6.0mm			
Length	DoV	FoV	Mirror tube
245mm	-7° bis 133°	45°	370°
315mm	-7° bis 133°	45°	370°
385mm	-7° bis 133°	45°	370°
455mm	-7° bis 133°	45°	370°
945mm	-7° bis 133°	45°	370°

#### Ø 8.0mm

Length	DoV	FoV	Mirror tube
115mm	-7° bis 133°	45°	370°
185mm	-7° bis 133°	45°	370°
255mm	-7° bis 133°	45°	370°
325mm	-7° bis 133°	45°	370°
395mm	-7° bis 133°	45°	370°
465mm	-7° bis 133°	45°	370°
605mm	-7° bis 133°	45°	370°

#### Ø 9.0mm

Length	DoV	FoV	Mirror tube
205mm	-7° bis 133°	45°	370°
305mm	-7° bis 133°	45°	370°
405mm	-7° bis 133°	45°	370°
505mm	-7° bis 133°	45°	370°
605mm	-7° bis 133°	45°	370°
705mm	7° bis 133°	45°	370°