

www.iteworld.com

iCONCEPTS
IMAGING SOLUTIONS

iLED PRO

Videoscope System




Technical data

iCAPTURE PRO

Display size: 7.0"
 Display resolution: 1024x600 Pixel
 Operating system: EIOS (Endoscopic Imaging Operating System)
 interface: USB
 Power supply, primary: Rechargeable Li-ion battery
 Power supply, secondary: 12V adapter (optional accessories)
 Storage: intern 16GB / USB (16GB in delivery)
 Video format: MPEG4 (.avi)
 Image format: BMP (.bmp), JPEG (.jpg), PNG (.png)


OTHER DATA

Ergonomics: rotatable + swiveling
 Weight: 1.28Kg
 Dimensions: see below
 Housing: Rugged PU with rubber shock protection
 System operating temperature: -25°C to +46°C
 Storage temperature: -25°C to +60°C
 Relative humidity: 95% less than - non condensing
 Sensor: High resolution Super HAD CCD image sensor



iLED PRO Videoendoscope

PROBES (mm)	4.0	6.0	8.0
Working length (m)	1.0 - 4.0	1.0 - 7.5	1.0 - 7.5
Articulation	4-way	4-way	4-way
Integrated objective lens	•	-	-
Interchangeable objective lens	-	•	•
Side view adapter	•	•	•



Probe	DOV	FOV	DOF	CODE
4.0mm	0°	60°	7-50mm	
4.0mm	0°	60°	4-10mm	SD
4.0mm	0°	90°	15mm-∞	
4.0mm	0°	90°	10-30mm	SD
4.0mm**	90°	60°	5-45mm	SVTA
6.0mm	0°	60°	5mm-∞	BLACK
6.0mm	0°	60°	8mm-∞	YELLOW-B
6.0mm	0°	90°	5mm-∞	RED
6.0mm	0°	120°	3mm-∞	GREEN
6.0mm**	90°	60°	5-15mm	SVTA-CF
6.0mm**	90°	60°	15-50mm	SVTA-FF
8.0mm	0°	28°	25mm-∞	BLUE
8.0mm	0°	60°	5mm-∞	BLACK
8.0mm	0°	60°	8mm-∞	YELLOW-B
8.0mm	0°	90°	8mm-∞	SILVER-B
8.0mm	0°	90°	5mm-∞	RED
8.0mm**	90°	60°	5mm-∞	SVTA
8.0mm	0°	90°	8mm-∞	SILVER-B
8.0mm	0°	90°	5mm-∞	RED
8.0mm**	90°	60°	5mm-∞	SVTA

